

ITEM	DESCRIPTION	PACK
------	-------------	------

A. PROTECTIVE COATING *

Water emulsion finish protects synthetic sports floors, enhances their appearance, and makes them easier to clean and maintain. Stands up to scuffing, scratching, rubber burns, and heel marks. Rubber burns, scuffs, and dirt are held on the surface of the film where they can be easily removed. Outstanding detergent resistance. Average coverage rate: 2000 square feet per gallon.

HIL0029006	1 gal.	4
HIL0029007	5 gal.	1

B. ONE PLUS® *

New and improved zinc-free floor polish contains no heavy metals and is durable, easy to use, and delivers a deep gloss. Stands up to scuffing, scratching, and black heel marks even in critical high traffic areas. Maintains both resilient and hard surface floors. Formulated to be "stackable" - you can apply multiple coats in one day. Excellent detergent resistance. Average coverage rate: 2000 square feet per gallon.

HIL0052706	1 gal.	4
HIL0052707	5 gal.	1
HIL0052709	55 gal.	1

C. SATIN FLOOR FINISH

Designed for low maintenance floor care programs, Satin Floor Finish is recommended for assisted living, and nursing homes, especially those that are dedicated to the care of Alzheimer's patients. Also for other situations where a low gloss surface or minimal reflection is desired. It provides a durable long life coating that is easy to maintain. No buffing required or desired.

HIL0054006	1 gal.	4
------------	--------	---

* Classified by Underwriters Laboratories, Inc.® as to slip resistance (186S).




This product meets Green Seal's environmental standard for industrial and institutional cleaners based on its reduced human and aquatic toxicity and reduced smog production potential.

HILLYARD TRILOGY®

The Systems Approach To Resilient Floor Care


Each Trilogy® program specifies quality seals and polishes to provide consistent performance and maximize the efforts of your staff. Trilogy's systemized approach takes into consideration the type of equipment you have and the amount of time you can dedicate to maintaining your resilient flooring.

By utilizing the systems that best meets your needs, the HILLYARD TRILOGY approach to floor care will allow you to keep the resilient flooring in your facility at a high-level of appearance while managing your maintenance operation on a cost effective basis. For detailed information, please refer to the TRILOGY section of this catalog.

ITEM	DESCRIPTION	PACK
A. SUPER HIL-BRITE® *		
	Self-polishing, water emulsion wax made of 100% prime Carnauba; the hardest, toughest natural wax known. Excellent resistance to problem heel marks. Delivers a deep, lustrous shine that buffs back easily - even after years of repeated wear and cleaning. Doesn't yellow with age. Average coverage per gallon of 2,000 square feet.	
HIL0050006	1 gal.	4
HIL0050007	5 gal.	1
HIL0050009	55 gal.	1



B. NEUTONE® *		
	Unique, waterless, four-in-one product cleans, seals, waxes, and conditions wood or cork floors in one simple operation. Safeguards against water damage to wood and cork floors. It has a natural affinity to wood and performs as an excellent conditioner. Buffs to a deep luster. Displays outstanding durability and delivers optimum protection to floors subjected to heavy traffic. Average coverage rate: 1,200 square feet per gallon.	
HIL0021606	1 gal.	6



C. SEAL 341® *		
	Enhances the rich, natural colors of hard floors without leaving a shiny, plastic-looking surface. Also seals resilient tile floors to create a smooth, unbroken base for high speed finishes. Protects all floors from dirt, spills, and abrasions that come from heavy traffic. It can be applied as a seal/finish to terrazzo, unglazed ceramic, quarry tile, concrete, paver brick, unpolished marble, slate, natural stone, resilient tile, and synthetic sports floors. Dries fast (less than one hour). Average coverage of 1000-1500 square feet per gallon.	
HIL0034106	1 gal.	4
HIL0034107	5 gal.	1
HIL0034109	55 gal.	1



* Classified by Underwriters Laboratories, Inc.® as to slip resistance (186S).



Hillyard's Green Select products are formulated to minimize the impact on the environment, reduce the risk to human health and at the same time improve worker safety.



ITEM	DESCRIPTION	PACK
------	-------------	------

A. PENETRATING SEAL NO. 21 *

A 35% premium tung oil oleoresinous seal that penetrates deep into wood to form a smooth, durable surface to seal out dirt and stains. Withstands heavy duty use as it enhances the beauty of your floor, even after months of wear and repeated cleaning. Perfect for coating parquet floors, strip or plank flooring, wood classrooms, and wood warehouse or factory floors. Ideal base for polishes and buffable waxes. Covers an average 350-500 square feet per gallon.

HIL0033306	1 gal.	6
HIL0033307	5 gal.	1

B. STRONG GUARD® *

Provides a stain-resistant base that withstands staining caused by Betadine®, Kool-Aid®, ketchup, mustard, beer, wine, motor oil, tar, asphalt, lipstick, ink, shoe polish, rust, and grease. The clear, protective seal layer enhances the original color of your floors and provides a smooth, tough base to help polishes form an unbroken surface for longer wear properties. Provides excellent protection for almost any sealable floor area. Covers an average of 1200-2000 square feet per gallon.

HIL0034506	1 gal.	4
HIL0034507	5 gal.	4
HIL0034509	55 gal.	1

C. TERRAZZINE® *

Zinc-free, transparent, fast drying seal/undercoater formulated for porous masonry floors like terrazzo and Saltillo tile. Terrazine® is "internally plasticized" to do a better job of filling the porosity of the floor, providing a smooth base for floor polish. It is tolerant of cold floors where conventional seals will not stand up. It can be applied to cold masonry floors (50°F or higher). Contains no heavy metals (a potential issue for sewage treatment facilities). Average coverage of 1000-1500 square feet per gallon.

HIL0033806	1 gal.	4
HIL0033807	5 gal.	1
HIL0033809	55 gal.	1

D. LOK-GARD® *



Specially formulated seal/finish enhances the rich, natural color of marble floors. Treated floors resist scuffing, scratching, black heel marks, and discoloration, even in high traffic areas. For all types of marble. Especially designed for highly polished marble. Easy to apply. Average coverage rate: 2,500 square feet per gallon.

HIL0033906	1 gal.	4
------------	--------	---

* Classified by Underwriters Laboratories, Inc.® as to slip resistance (186S).



Hillyard's Green Select products are formulated to minimize the impact on the environment, reduce the risk to human health and at the same time improve worker safety.

ITEM DESCRIPTION PACK

A. HIL-TEX®+ *

Zinc-free, transparent, fast-drying, seal/undercoater seals porous flooring. Provides a smooth, tough base that helps polishes form an unbroken surface film for longer wear properties. Dries quickly. Highly resistant to grease, oil, detergents, and ultraviolet rays. Provides optimum protection for almost any sealable floor. Covers between 1200-2000 square feet per gallon.

HIL0034406	1 gal.	4
HIL0034407	5 gal.	1
HIL0034409	55 gal.	1



B. ONEX-SEAL® II *

Penetrating seal/finish enhances the beauty of your hard floors while it protects against excessive wear and scuffing. Dries quickly and buffs easily to a rich, deep luster. Gives your floors a soft, yet durable shine. Ideal for use on hard floors like terrazzo, concrete, and unpolished marble. Approved by the National Terrazzo and Mosaic Association. Average coverage rate: 800-1200 square feet per gallon.

HIL0031506	1 gal.	6
HIL0031507	5 gal.	1



C. H.R. 2000® *

High gloss restorer delivers a deep gloss while it protects your base coat and keeps traffic lanes, heel marks, and scuffing to a minimum. Resists powdering caused by the heat and friction generated with ultra-high speed equipment. Contains no heavy metals, making H.R. 2000® an excellent choice to complement a zinc-free floor maintenance program. Economical coverage of 8,000-10,000 square feet per gallon.

HIL0053804	1 qt.	12
HIL0053806	1 gal.	4
HIL0053807	5 gal.	1

D. RESTORER *

Delivers a deep gloss and extends the life of your floor finish. Protects your base coat and keeps traffic lanes, heel marks, and scuffing to a minimum, while restoring gloss to maximum levels. Resists powdering and extends the time between refinishing. It can be used in an auto scrubber. Contains no heavy metals.

Complements a zinc-free floor maintenance program. Average coverage rate: 8,000-10,000 square feet per gallon.

HIL0053904	1 qt.	12
HIL0053906	1 gal.	4
HIL0053907	5 gal.	1
HIL0053909	55 gal.	1



E. HIL-GLO® *

Spray buff compound gives floors a durable, high gloss quickly and easily. Delivers maximum gloss while it cleans. Special thermoplastic resins provide resistance to black heel marks, scuffs, and scratching. Ideal for spray buffing resilient tile and hard floors. Compatible with most quality metal interlocks.

HIL0053306	1 gal.	4
-------------------	--------	---

* Classified by Underwriters Laboratories, Inc.® as to slip resistance (186S).



Hillyard's Green Select products are formulated to minimize the impact on the environment, reduce the risk to human health and at the same time improve worker safety.

A Note About Slip Resistance...

Slip resistance is an important property of any floor coating. All Hillyard resilient floor seals, waxes, polishes and cleaners are classified by Underwriters Laboratories, Inc.® as to slip resistance. The test procedure which is followed (ASTM D2047) measures the static coefficient of friction as determined by the James Machine.

Before a particular product will pass the test, the static coefficient of friction must be greater than 0.5.

At Hillyard, quality control begins with the raw materials and doesn't stop until the final product is packaged. Our company was founded on quality over 100 years ago, and the control measures we take assure you that we deliver what we promise.