



RESILIENT FLOORING
Includes Asphalt, Rubber, Vinyl, Vinyl Composition, And Linoleum Tile.

RESILIENT FLOORING Preparation

New Floors After flooring is laid and the adhesive has dried, (usually two weeks) scrub with a solution of POWER-STRIP® (10 ounces POWER-STRIP® per gallon of water) to remove any factory finishes. Pick up with wet vac and neutralize with solution of NUTRA-RINSE®. Pick up NUTRA-RINSE® solution and follow by damp mop rinsing several times with clean water. Let floor dry at least one hour.

Old Floors Select Hillyard STRIP-ALL®, ASSAULT®, or DEVASTATOR® depending on the TRILOGY® SYSTEM being utilized. Scrub floor using selected stripper at appropriate dilution rate with black stripping pads. Pick up stripping solution with wet vac and neutralize floor with NUTRA-RINSE®. Pick up NUTRA-RINSE® solution and finish by damp mop rinsing the floor twice with clean water. Allow floor to dry at least one hour before applying finish.

RESILIENT FLOORING Sealing/Finishing

TRILOGY® SYSTEM I

When floor is clean and dry apply one or two even coats of HIL-TEX+® or SEAL 341 using a clean synthetic mop with a minimum of 30 minutes between coats. If staining is a problem, STRONG GUARD® stain-resistant seal should be considered. Apply TOP SHAPE® or EXPLORER® following label directions.

TRILOGY® SYSTEM II

When floor is clean and dry apply one or two even coats of HIL-TEX+ or SEAL 341 using a clean synthetic mop with a minimum of 30 minutes between coats. If staining is a problem, STRONG GUARD® stain-resistant seal should be considered. Apply ENDEAVOR® or NORTH STAR® following label directions.

TRILOGY® SYSTEM III

When floor is clean and dry apply one or two even coats of HIL-TEX+ or SEAL 341 using a clean synthetic mop with a minimum of 30 minutes between coats. If staining is a problem, STRONG GUARD® stain-resistant seal should be considered. Apply RESILIENCE® following label directions.

Buffable Program

Apply two coats of SUPER HIL-BRITE® or HIL-SHEEN® following label directions.

Resilient Flooring Daily/Weekly Maintenance

Dust mop and damp mop or autoscrub according to the maintenance schedule outlined for each TRILOGY® SYSTEM.