

Jell Baseboard Stripper

A heavy-duty stripper for build-up on baseboards and in corners or other hard-to-reach areas. The clinging gel provides extra penetration power to lift off even the heaviest accumulations of wax without damaging the original surface or finish. Inverted valve makes for easy application.

Features & Benefits

- Floors, Baseboards, Ceramic Wall Tile
- Clinging Foam Adheres to Surfaces
- Easy Rinsing

Directions For Use

1. Shake well before using.
2. Check the product on a small inconspicuous area of the surface to be de-waxed to make sure there is no attack. Do not spray on painted or varnished surfaces. Wipe off any overspray immediately.
3. Turn can UPSIDE DOWN and hold 6-10 inches from baseboard or surface to be sprayed. A thin even coating should cover the wax.
4. Wait 3 to 5 minutes, longer in case of substantial build-up. Wet scrub the surface with an abrasive pad or scrub brush. Repeat until all wax is removed.
5. Rinse surface with clean water and allow area to dry thoroughly before re-polishing.

Certifications, Registrations & Notes

NSF Certified C1

PO Box 909
St. Joseph, MO 64502
800.365.1500
www.hillyard.com



Safety

See material safety data sheet and product label for safety information, handling and proper use.

Physical Characteristics

Color	Pale beige
Fragrance	Pine

Technical Specifications

Ozone Depleting Compound	None
Recyclable Package	Yes
VOC Compliant CARB	Yes
VOC Compliant OTC	Yes
Labeled Flammable	No
pH	11.50 - 12.50

Availability

Item	Pack
HIL0103655	12 - 19 oz. Cans

HILLYARD
The Cleaning Resource®