



ASSAULT®

MOP-ON STRIPPER FOR REMOVAL OF WAXES AND POLYMERS

READY TO USE #149

HMIS Rating: Health = 2, Flammability = 0, Reactivity = 0

DANGER

CONTAINS: ETHANOLAMINE (CAS #141-43-5); SODIUM METASILICATE (CAS #6834-92-0); WATER (CAS #7732-18-5); SODIUM XYLENE SULFONATE (CAS #1300-72-7); ETHYLENE GLYCOL MONOPHENYL ETHER (CAS #122-99-6); 1-BUTOXY-2-PROPANOL (CAS #5131-66-8).

Corrosive. Do not get in eyes, on skin, or on clothing. USE WITH ADEQUATE VENTILATION. Avoid prolonged breathing of vapors. Open windows and doors, use exhaust fans or other means to **insure fresh air entry during application and drying.** Refer to OSHA STANDARD 29 CFR 1910.94 for technical guidelines on keeping air contamination below acceptable exposure limits. Wash thoroughly after handling. Do not take internally. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local applicable regulations.

PERSONAL PROTECTIVE EQUIPMENT: When there is a danger of contact with the concentrate use chemical safety goggles and impervious gloves. Wear impervious/slip-resistant boots such as Hillyard Stripping Boots while standing in the stripping solution.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing. Get medical attention. Wash clothing before reuse. If swallowed, do not induce vomiting; immediately give large amounts of water and CALL A PHYSICIAN, hospital emergency room or poison control center. Inhalation: Remove victim to fresh air; if respiratory tract remains irritated call a physician.

See Material Safety Data Sheet for additional information.

DANGER

CAUSES EYE BURNS -- HARMFUL IF SWALLOWED

KEEP OUT OF REACH OF CHILDREN

(See Manufacturer's Label for Additional Information.)

Customer Affixed Label

"CHECKERBOARD" Trademark®



HILLYARD INDUSTRIES, St. Joseph, MO 64502 USA – Tele.: 816-233-1321 – www.hillyard.com

0109