### Lok-Gard<sup>®</sup> Marble Finish

A specially formulated seal/finish designed to enhance the rich, natural color of marble floors. A Lok-Gard treated floor resists scuffing, scratching, black heel marks, and discoloration, even in high traffic areas. It can be used on all types of marble and is especially designed for highly polished marble.

### **Features & Benefits**

- Enhances the rich natural color of marble floors.
- Resists scratches, black heel marks, and discoloration.
- Makes daily/weekly maintenance much easier.

### **Directions**

#### **DIRECTIONS FOR USE:**

**NEW FLOORS:** Scrub with Hillyard Super Shine-All or Citrus-Scrub and a red pad. Pick up scrubbing solution with a wet vacuum, automatic scrubber, or mop. Damp mop rinse with clear water twice; allow the floor to dry at least 1 hour.

**OLD FLOORS:** Remove old finishes, residues, and dirt using a solution of Devastator. Scrub the floor with a red pad and a 175 rpm floor machine. Pick up the scrubbing solution with a wet-vac, automatic scrubber, or mop. Flood rinse the floor with clear water and pick up; damp mop rinse with clear water twice. Allow the floor to dry at least one hour. For extremely heavy buildup, or areas inaccessible by floor machines, use Hillyard Devastator.

**APPLICATION:** When the floor is thoroughly clean and dry, apply Lok-Gard with a clean synthetic mop. Under normal conditions, apply 1 to 4 thin coats of Lok-Gard allowing one hour between coats. No more than 4 coats should be applied within a 24-hour period. Temperature, humidity, and air movement affect curing times. After final coat has dried, burnish floor using a high speed machine and Hillyard 100-D Neutral Polythermal Pad. Dust mop immediately with Hillyard Super Hil-Tone treated dust mop.

MAINTENANCE: Dust mop daily with Hillyard Super Hil-Tone treated dust mop. Mop or automatic scrub with Super Shine-All or Top Clean as needed, Always use red or white colored pads with the automatic scrubber. (Do not use aggressive brushes or pads on marble.) For spray buffing, use Hillyard Hil-Glo, Hillyard Restorer, or H.R. 2000. Periodically floor may be dry burnished using a high speed machine and Hillyard 100-D Neutral Polythermal Pad, Floor may be scrubbed with a solution of Super Shine-All or Top Clean and recoated as needed. **NOTICE: Do not use Hillyard Power-Strip or Nutra-Rinse on marble floors.** Proper curing between coats prevents pulling or streaking. Best results are obtained with adequate ventilation and floor temperatures above 60°F (16°C). Do not pour unused material back into container.

### **Certifications, Registrations & Notes**

Classified by Underwriters Laboratories, Inc.® as to slip resistance. (1865).

## FLOOR CARE



### Safety

See material safety data sheet and product label for safety information, handling and proper use.

HMIS Concentrate/R1	
Health	0
Flammability	0
Reactivity	0

### **Technical Specifications**

Non-Objectionable
Non objectionable
Milky Emulsion
8.00 - 9.00
16.00%
RTU

### Availability

Item	Pack
HIL0033906	4 - 1 Gallon Containers

# HILLYARD ------

P.O. Box 909 t. Joseph, MO 64502 1-800-365-1555 www.hillyard.com