

# Expediter® II

HILLYARD  
**TRILOGY**  
SYSTEM I

A high solids floor polish modified with urethane for outstanding scuff resistance, gloss, and durability. Expediter II provides exceptional resistance to black heel marks, scuffing, and scratching. Daily and weekly maintenance is simple with Expediter II. It is formulated to take heavy traffic and still come out shining. Daily dust mopping and occasional damp mopping or spray buffing keeps your floors looking beautiful.

## Features & Benefits

- Dries to a clear, beautiful high gloss without buffing.
- Urethane fortified for excellent durability.
- Designed for limited maintenance floor care programs.

## Directions

**PREPARATION:** Strip other finishes from the floor with HILLYARD DEVASTATOR, SUPER STRIP, or POWER-STRIP following label directions. Use floor machine with black pad or brush (do not use abrasive pads on tile containing asbestos). Remove stripping solution with a wet vacuum. Heavy rinse with HILLYARD NUTRA-RINSE mixed 4 oz. per gallon of water and pick up with the wet vacuum. Damp mop all flooring twice with clean, cool water. Allow the floor to dry.

**APPLICATION:** On newer floors, a sealer is not necessary. Apply a minimum of 5 coats of EXPEDITER II with a flat mop applicator or clean synthetic mop. Allow each coat to dry a minimum 35 minutes before applying the next. If a sealer is not used and the floor is porous, apply a minimum of 6 coats of EXPEDITER II.

**NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60°F (16°C).

**FLOOR PAD RECOMMENDATIONS:** Strip - black; Spray Buff - red followed by white; Scrub and Recoat - blue or green; Autoscrubbing - red.

**NOTICE:** Do not use an ammoniated cleaner for daily care. If the floor is extremely porous, seal with HILLYARD HIL-TEX+ or SEAL 341 before applying EXPEDITER II. If stains are a problem, seal with STRONG GUARD.

**NOTE:** Keep container closed when not in use. Do not pour unused finish or seal back into the original container.

## Certifications, Registrations & Notes

Classified by Underwriters Laboratories, Inc.® as to slip resistance. (186S).



## Safety

See material safety data sheet and product label for safety information, handling and proper use.

### HMIS

	Concentrate
Health	0
Flammability	0
Reactivity	0

### Technical Specifications

Color	White
Scent	Non-Objectionable
Appearance	Milky Emulsion
pH (concentrate)	8.50 - 9.50
Non-Volatile Matter	18.00%
Dilution Rate	RTU

### Availability

Item	Pack
HIL0053106	4 - 1 Gallon Containers
HIL0053107	1 - 5 Gallon Bag-In-Box
HIL0053109	1 - 55 Gallon Drum

**Coverage Rates:** 1,500 - 2,000 Sq. Ft. per Gallon  
*Rates can vary greatly based on surface and application method.*

HILLYARD

P.O. Box 909  
St. Joseph, MO 64502  
1-800-365-1555  
www.hillyard.com